

EMAIL info@ScanWide.com for QUOTE!

- COLOR OVERHEAD BOOK SCANNER FOR FORMATS UP TO DIN/ISO A1+8%
- TRUE SCAN TECHNOLOGY, NOT A DIGICAM SUBSTITUTE
- 600 x 600 DPI SCANNER RESOLUTION
- < 3 SEC. FOR A1 SCAN @ 200 DPI
- MOTORIZED BOOK CRADLE WITH LIFT UP TO 10 CM
- GLASS PLATE FOR
 PERFECT SCANS IN FLAT
 MODE
- V SHAPED BOOK CRADLE
- SCAN CLIENT INTERFACE
- DIGITAL COLOR BALANCE
- INTEGRATED ICC PROFILE
- USER INTERFACE CONFIGURABLE IN YOUR LANGUAGE
- INTEGRATED 64BIT LINUX, INTEL I3 QUAD CORE, 8 GB RAM, 320GB HDD
- GIGABIT TCP/IP NETWORK
 INTERFACE
- SUPPORTS SRGB, ADOBE RGB, NATIVE COLOR SPACES
- VIRUS RESISTANT LINUX OPERATING SYSTEM
- EXCELLENT ENERGY EFFICIENCY
- EASY INSTALLATION VIA SCAN2NET[®] TECHNOLOGY



Bookeye[®] 4 V1A Professional is the wide format scanner for digitization projects with formats up to 33.5" X 25"

Productivity meets quality in digitization!

Bookeye[®] 4 V1A Applications :

- Archiving documents from government agencies, registries, universities and nonprofit organizations
- Scanning newspapers, periodicals, catalogs and magazines
- Digitizing paper sheets directly from file folders
- Digitizing bound and stapled documents
- Preserving books and sensitive historical documents

NEW! Large Format Book Scanner Complete ScanStation Solution Scan to Network, USB, Tablet, Phone or Device No PC Required! (Apple iOS and Android Compatible)

ScanWide.com

Bookeye[®]4 V1A is the world's first and only A1+ scanner that accommodates both flat documents - with or without the glass plate; as well as large, fragile bound documents, using the protective V cradle.

Bookeye[®] 4 V1A is suitable for digitization projects that require high quality and maximum productivity, even in 24/7 operation. Originals up to A1+, such as books, magazines, posters, folders or bound documents of all kinds, can be digitized by the Bookeye[®] 4 V1A at unsurpassed scanning speed.



TECHNICAL DATA

EMAIL info@ScanWide.com for QUOTE!

| Maximum Scan Area | 635 x 850 mm (25 x 33.5 inch), 8% more than DIN/ISO A1 |
|--------------------------|---|
| Scanner Resolution | 600 x 600 dpi |
| Scan Speed | A1 @ 150 dpi: 1.8 s |
| | A1 @ 200 dpi: 2.3 s |
| | A1 @ 300 dpi: 5.3 s |
| | A1 @ 400 dpi: 7.0 s |
| Color Depth | 36 bit color / 12 bit grayscale |
| Scan Output | 24 bit color, 8 bit grayscale, bitonal, enhanced halftone |
| File Formats | PDF, PDF/A, JPEG, PNM, TIFF uncompressed, TIFF G4 (CCITT), Multipage PDF, TIFF |
| ICC Profiles | Embedded for sRGB, Adobe RGB and native. Individual profiling via web based Scan2ICC subscription |
| Camera | CCD camera |
| Light Source | White LEDs, according IEC 60825-1: class 1, no IR/UV emission |
| Lamp Life Time | 50,000 h (typ.) |
| Computer | 64 bit Linux, Intel quad core processor, 8 Gigabyte RAM, 320GB HDD for extra large jobs |
| Interface | 1 GBit Fast Ethernet with TCP/IP based Scan2Net [®] Interface |
| Dimension | 1100 x 880 x 855 mm (43.3 x 34.6 x 33.7 inch) (H x W x D) |
| Weight | 77 kg / 170 lbs. |
| Electrical Specification | 100-240 V AC, 47 - 63 Hz (external power supply, complies with ECO standard CEC level V) |
| Power Consumption | ≤ 0.5 W (Sleep) / 2.5 W (Standby) / 130 W (Scanning) |
| Operating Temperature | 5 to 40 °C, 40 to 105 °F |
| Relative Humidity | 20 to 80 % (non-condensing) |
| Noise | 55 dB(A)(Book cradle motor working) / < 42 dB(A) (Scanning) / < 33 dB(A) (Standby) |
| | ANSI/UL 60950-1, CAN/CSA C22.2 No. 60950-1; IEC 60950-1; GB4943.1-2011, GB9254-2008, |
| Approvals | GB17625.1-2012; IS 13252-1:2010; EN 55022, EN 55024; FCC 47 Part 15 |
| | |

WEEE



Intertek IEC 60950-1 Intertek



CE F©

Visit our homepage!



RoHS

(800) 681-8520 info@scanwide.com